

023



050






051



081

Hiber

N° Teglie Interasse mm	Modello Abbattitore	Dimensioni mm	Abbattimento	Temperatura al cuore °C	Tensione di alimentazione Volt	Potenza totale Watt *	Resa** kg/H
3 x Teglie (354x325)	ABM 023 S	560x595x520h	MISTO	+90 +3 • +90 -18	AC 230 50 Hz	960	5
 5 x (600x400)	PDM 050 E	790x700x800h	MISTO	+90 +3 • +90 -18	AC 230 50 Hz	1000	8
Abbattitore da incasso (senza piano)							
 5 x (600x400)	PDM 051 S	790x700x850h	MISTO	+90 +3 • +90 -18	AC 230 50 Hz	1200	10
	PCM 051 S	790x700x850h	MISTO	+90 +3 • +90 -18	AC 230 50 Hz	1400	15
 8 x (600x400)	PCM 081 S	790x800x1320h	MISTO	+90 +3 • +90 -18	AC 230 50 Hz	2100	24
	PCM 081 T	790x800x1320h	MISTO	+90 +3 • +90 -18	AC 230 50 Hz	2100	24

Sonda di temperatura riscaldabile DI SERIE

* Potenza elettrica massima in Watt: -10°C/+55°C.

** Su croissant crudo da 60 gr. non lievitato a -18°C al cuore

Pasticceria e Panetteria